















ESD

TVS

MOS

LDO

Diode

Sensor

DC-DC

Product Specification


Domestic Part Number	PESD24VS2UT
Overseas Part Number	PESD24VS2UT
▶ Equivalent Part Number	PESD24VS2UT





Features

- 300 W peak pulse power (tp = $8/20\mu$ s)
- Bidirectional and unidirectional configurations
- Solid-state silicon-avalanche technology
- Low clamping voltage
- Low leakage current
- IEC 61000-4-2 ±30kV contact ±30kV air
- IEC 61000-4-4 (EFT) 40A(5/50ns)
- IEC 61000-4-5 (Lightning) 6A(8/20μs)



Applications

- Dataline
- Automatic Teller Machines
- Net works
- Power line

Mechanical Data

■ SOT-23 package

■ Molding compound flammability rating: UL 94V-0

■ Packaging: Tape and Reel

■ RoHS/WEEE Compliant

Absolute Maximum Rating

Rating	Symbol	Value	Units
Peak Pulse Power (t _p =8/20μs)	P _{PP}	300	W
Peak Pulse Current (t _p =8/20μs)(note1)	I_{pp}	6	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	$ m V_{ESD}$	30 30	kV
Lead Soldering Temperature	$T_{ m L}$	260	$^{\circ}$
Junction Temperature	TJ	-55 to + 125	$^{\circ}$
Storage Temperature	T_{stg}	-55 to + 125	$^{\circ}$




Electrical Characteristics

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-OffVoltage	V_{RWM}				24	V
Reverse Breakdown Voltage	V_{BR}	I _T =1mA	26.7	30.0	34.0	V
Reverse Leakage Current	I_R	V _{RWM} =24V,T=25°C		0.1	0.5	μΑ
Peak Pulse Current	I_{PP}	tp =8/20μs			6	A
Clamping Voltage	V _C	$I_{PP}=6A, t_p=8/20 \mu s$			44	V
Junction Capacitance	Cj	$V_R = 0V, f = 1MHz$ (Pin1 \cdot Pin2 to Pin 3)		30	35	pF

Electrical Parameters (TA = 25°C unless otherwise noted)

Symbol	Parameter
Ірр	Maximum Reverse Peak Pulse Current
Vc	Clamping Voltage @ Ipp
V _{RWM}	Working Peak Reverse Voltage
Ir	Maximum Reverse Leakage Current @ VRWM
V_{BR}	Breakdown Voltage @ IT
Iτ	Test Current



Note:. $8/20\mu s$ pulsewaveform.



TypicalCharacteristics

Figure 1: Peak Pulse Power vs. Pulse Time




Figure 2: Power Derating Curve




Figure3: Pulse Waveform




Figure 4: Clamping Voltage vs.lpp






Figure 5: Peak Pulse Power Vs Junction Temperature




Copyright@ 歷芯半導體 3 http://www.evvosemi.com/



Outline Drawing - SOT-23








DIMENSIONS				
SYMBOL	MILLIMETER		INCHES	
OTHEOL	MIN	MAX	MIN	MAX
Α	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
D	2.800	3.000	0.110	0.118
b	0.300	0.500	0.012	0.020
E	2.250	2.550	0.089	0.100
E1	1.200	1.400	0.047	0.055
е	0.950 BSC		0.037	7 BSC
L	0.300	0.500	0.012	0.020
θ	0	8°	0	8°

Marking



Ordering information

Order code	Package	Base qty	Delivery mode
PESD24VS2UT	SOT-23	3000	Tape and reel



Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.