

# EVVOSEMI<sup>®</sup>

THINK CHANGE DO




ESD




TVS




MOS



LDO



Diode



Sensor



DC-DC

## Product Specification

▶ Domestic	Part Number	FDN340P
▶ Overseas	Part Number	FDN340P-EV
▶ Equivalent	Part Number	FDN340P

EV is the abbreviation of name EVVO

## SOT-23 Plastic-Encapsulate MOSFETS

### FDN340P

### P-Channel 20-V(D-S) MOSFET

V(BR)DSS	RDS(on)MAX	ID
-20 V	70mΩ@ -4.5V	-2A
	110mΩ@ -2.5V	
	210mΩ@ -1.8V	


#### FEATURE

- TrenchFET Power MOSFET
- Supper high density cell design


#### APPLICATION

- ※ Battery protection
- ※ Load switch
- ※ Battery management


#### MARKING



#### Equivalent Circuit



#### SOT - 23



1. GATE
2. SOURCE
3. DRAIN

#### Maximum ratings ( Ta=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	VDS	-20	V
Gate-Source Voltage	VGS	±8	
Continuous Drain Current	ID	-2	A
Pulsed Diode Current	IDM	-10	
Power Dissipation	PD	1.1	W
Thermal Resistance from Junction to Ambient (t≤10s)	RθJA	250	°C/W
Operating Junction	TJ	150	°C
Storage Temperature	TSTG	-55~+150	°C

## SOT-23 Plastic-Encapsulate MOSFETS

### MOSFET ELECTRICAL CHARACTERISTICS

Static Electrical Characteristics (Ta = 25 °C Unless Otherwise Noted)


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static</b>						
Drain-source breakdown voltage	V(BR)DSS	VGS = 0V, ID = -250 $\mu$ A	-20			V
Gate-source threshold voltage	VGS(th)	VDS = VGS, ID = -250 $\mu$ A	-0.4		-1.5	V
Gate-source leakage	IGSS	VDS = 0V, VGS = $\pm$ 8V			$\pm$ 100	nA
Zero gate voltage drain current	IDSS	VDS = -16V, VGS = 0V			-1	$\mu$ A
Drain-source on-state resistancea	RDS(on)	VGS = -4.5V, ID = -2A		52	70	m $\Omega$
		VGS = -2.5V, ID = -1.7A		78	110	m $\Omega$
		VGS = -1.8V, ID = -1.2A			210	m $\Omega$
Forward transconductancea	gfs	VDS = -4.5V, ID = -2A		8		S
Diode forward voltage	VSD	IS = -1A, VGS = 0V		-0.8	-1.2	V
<b>Dynamic</b>						
Input capacitance	Ciss	VDS = -10V, VGS = 0V, f = 1MHz		600		pF
Output capacitance	Coss			175		pF
Reverse transfer capacitanceb	Crss			80		pF
Total gate charge	Qg	VDS = -10V, VGS = -4.5V, ID = -2A		8		nC
Gate-source charge	Qgs			1.3		nC
Gate-drain charge	Qgd			2.2		nC
Gate resistance	Rg	f = 1MHz	0.5		3.2	$\Omega$
<b>Switchingbtr</b>						
Turn-on delay time	td(on)	VDS = -10V RL = 3.5 $\Omega$ , ID $\approx$ -1A, VGEN = -4.5V, Rg = 3 $\Omega$		6		ns
Rise time	tr			9		ns
Turn-off delay time	td(off)			31		ns
Fall time	tf			26		ns
<b>Drain-source body diode characteristicstr</b>						
Continuous Source-Drain Diode Current	IS	Tc = 25 $^{\circ}$ C			-1.2	A
Pulsed Diode forward Curren	ISM				-10	A

**Note :**

1. Repetitive Rating : Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t < 10 sec.
3. Pulse Test : Pulse Width  $\leq$  300 $\mu$ s, Duty Cycle  $\leq$  2%.
4. Guaranteed by design, not subject to production testing.

### SOT-23 Plastic-Encapsulate MOSFETS

SOT-23 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°



## Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.