

# EVVOSEMI<sup>®</sup>

THINK CHANGE DO



ESD



TVS



MOS



LDO



Diode



Sensor



DC-DC

## Product Specification

▶ Domestic	Part Number	AO3422A
▶ Overseas	Part Number	AO3422A
▶ Equivalent	Part Number	AO3422A

EV is the abbreviation of name EVVO

## N-Channel 60-V(D-S) MOSFET

V(BR)DSS	RDS(on)MAX	ID
60 V	105mΩ@10V	2.1A
	125mΩ@4.5V	



### FEATURE

※ TrenchFET Power MOSFET


### APPLICATION

- ※ Load Switch for Portable Devices
- ※ DC/DC Converter

### MARKING



### SOT - 23



1. GATE
2. SOURCE
3. DRAIN

### Maximum ratings ( Ta=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	VDS	60	V
Gate-Source Voltage	VGS	±20	
Continuous Drain Current	ID	2.1	A
Pulsed Diode Current	IDM	10	
Continuous Source-Drain Current(Diode Conduction)	IS	0.85	
Power Dissipation	PD	1.25	W
Thermal Resistance from Junction to Ambient (t≤5s)	RθJA	125	°C/W
Operating Junction	TJ	150	°C
Storage Temperature	TSTG	-55~+150	°C

## MOSFET ELECTRICAL CHARACTERISTICS


## Static Electrical Characteristics (Ta = 25 °C Unless Otherwise Noted)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static</b>						
Drain-source breakdown voltage	<b>V(BR)DSS</b>	VGS = 0V, ID = 250μA	60			V
Gate-source threshold voltage	<b>VGS(th)</b>	VDS = VGS, ID = 250μA	1		2.5	V
Gate-source leakage	<b>IGSS</b>	VDS = 0V, VGS = ±20V			±100	nA
Zero gate voltage drain current	<b>IDSS</b>	VDS = 60V, VGS = 0V			1	μA
Drain-source on-state resistancea	<b>RDS(on)</b>	VGS = 10V, ID = 3A		80	105	mΩ
		VGS = 4.5V, ID = 2A		89	125	mΩ
Forward transconductancea	<b>gfs</b>	VDS = 4.5V, ID = 2.1A		11		S
Diode forward voltage	<b>VSD</b>	IS=1.5A, VGS=0V		0.8	1.3	V
<b>Dynamic</b>						
Input capacitance	<b>Ciss</b>	VDS = 25V, VGS = 0V, f=1MHz		214	300	pF
Output capacitance	<b>Coss</b>			31		pF
Reverse transfer capacitanceb	<b>Crss</b>			12.6		pF
Total gate charge	<b>Qg</b>	VDS = 25V, VGS = 4.5V, ID = 3A		2.6	3.3	nC
Gate-source charge	<b>Qgs</b>			0.6		nC
Gate-drain charge	<b>Qgd</b>			0.8		nC
Gate resistance	<b>Rg</b>	f=1MHz		1.3	3	Ω
<b>Switchingb</b>						
Turn-on delay time	<b>td(on)</b>	VDS= 25V RL=6Ω, ID ≈ 1A, VGEN= 10V, Rg=3Ω		2.3		ns
Rise time	<b>tr</b>			2.4		ns
Turn-off delay time	<b>td(off)</b>			16.5		ns
Fall time	<b>tf</b>			2		ns
<b>Drain-source body diode characteristics</b>						
Continuous Source-Drain Diode Current	<b>IS</b>	Tc=25°C			3	A

**Note :**

1. Repetitive Rating : Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t < 5 sec.
3. Pulse Test : Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production testing.

## SOT-23 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
$\theta$	0°	8°	0°	8°

## Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.