

# EVVOSEMI<sup>®</sup>

THINK CHANGE DO



ESD



TVS



MOS



LDO



Diode



Sensor



DC-DC


## Product Specification

▶ Domestic	Part Number	PESDxxxL2UM
▶ Overseas	Part Number	PESDxxxL2UM
▶ Equivalent	Part Number	PESDxxxL2UM

EV is the abbreviation of name EVVO

## FEATURES

- Uni-directional ESD protection of two lines or bi-directional ESD protection of one line
- Reverse standoff voltage 3.3 and 5 V
- Low diode capacitance
- Ultra low leakage current
- Leadless ultra small SOT883 surface mount package (1 × 0.6 × 0.5 mm)
- Board space 1.17 mm<sup>2</sup> (approx. 10% of SOT23)
- ESD protection >15 kV
- IEC 61000-4-2; level 4 (ESD); 15 kV (air) or 8 kV (contact).



## APPLICATIONS

- Cellular handsets and accessories
- Portable electronics
- Computers and peripherals
- Communication systems
- Audio and video equipment.

## DESCRIPTION

Low capacitance ESD protection diode in a three pad SOT883 leadless ultra small plastic package designed to protect up to two transmission or data lines from ElectroStatic Discharge (ESD) damage.

## LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 60134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
<b>Per diode</b>					
I <sub>pp</sub>	peak pulse current	8/20 μs pulse; notes 1, 2 and 3	-	3	A
	PESD3V3L2UM			2.5	A
P <sub>pp</sub>	peak pulse power	8/20 μs pulse; notes 1, 2 and 3	-	30	W
I <sub>FSM</sub>	non-repetitive peak forward current	t <sub>p</sub> = 1 ms; square pulse	-	3.5	A
I <sub>ZSM</sub>	non-repetitive peak reverse current	t <sub>p</sub> = 1 ms; square pulse	-	0.9	A
	PESD3V3L2UM			0.8	A
P <sub>tot</sub>	total power dissipation	T <sub>amb</sub> = 25 °C; note 4	-	250	mW
P <sub>ZSM</sub>	non-repetitive peak reverse power dissipation	t <sub>p</sub> = 1 ms; square pulse; see Fig.4	-	6	W
T <sub>stg</sub>	storage temperature		-65	+150	°C
T <sub>j</sub>	junction temperature		-	150	°C
ESD	electrostatic discharge	IEC 61000-4-2 (contact discharge)	15	-	kV
		HBM MIL-Std 883	10	-	kV

1. Non-repetitive current pulse 8/20 μs exponential decay waveform; see Fig.5.
2. Pins 1 and 3 or 2 and 3.
3. Pins 1 and 2.
4. Device mounted on standard printed-circuit board.

**ESD standards compliance**

IEC 61000-4-2, level 4 (ESD)	>15 kV (air); >8 kV (contact)
HBM MIL-Std 883, class 3	>4 kV

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
R <sub>th j-a</sub>	thermal resistance from junction to ambient	all diodes loaded; note 1	500	K/W
		one diode loaded; note 2	290	K/W

1. Refer to SOT883 standard mounting conditions (footprint), FR4 with 60 μm copper strip line.
2. FR4 single-sided copper 1 cm<sup>2</sup>.

T<sub>j</sub> = 25 °C unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
<b>Per diode</b>						
V <sub>F</sub>	forward voltage	I <sub>F</sub> = 200 mA	–	1	1.2	V
V <sub>RWM</sub>	reverse stand-off voltage PESD3V3L2UM PESD5V0L2UM		–	–	3.3	V
			–	–	5	V
I <sub>RM</sub>	reverse leakage current PESD3V3L2UM PESD5V0L2UM	V <sub>R</sub> = 3.3 V	–	75	300	nA
		V <sub>R</sub> = 5 V	–	5	25	nA
V <sub>(CL)R</sub>	clamping voltage PESD3V3L2UM  PESD5V0L2UM	8/20 μs pulse				
		I <sub>pp</sub> = 1 A; notes 1 and 2	–	–	8	V
		I <sub>pp</sub> = 3 A; notes 1 and 2	–	–	12	V
		I <sub>pp</sub> = 1 A; notes 1 and 3	–	–	9	V
		I <sub>pp</sub> = 3 A; notes 1 and 3	–	–	13	V
		I <sub>pp</sub> = 1 A; notes 1 and 2	–	–	10	V
		I <sub>pp</sub> = 2.5 A; notes 1 and 2	–	–	13	V
		I <sub>pp</sub> = 1 A; notes 1 and 3	–	–	11	V
V <sub>BR</sub>	breakdown voltage PESD3V3L2UM PESD5V0L2UM	I <sub>Z</sub> = 1 mA	5.32	5.6	5.88	V
			6.46	6.8	7.14	V
S <sub>Z</sub>	temperature coefficient PESD3V3L2UM PESD5V0L2UM	I <sub>Z</sub> = 1 mA	–	1.3	–	mV/K
			–	2.9	–	mV/K
r <sub>diff</sub>	differential resistance PESD3V3L2UM PESD5V0L2UM	I <sub>R</sub> = 1 mA	–	–	200	Ω
			–	–	100	Ω
C <sub>d</sub>	diode capacitance PESD3V3L2UM  PESD5V0L2UM	f = 1 MHz; V <sub>R</sub> = 0	–	22	28	pF
		f = 1 MHz; V <sub>R</sub> = 5	–	12	17	pF
		f = 1 MHz; V <sub>R</sub> = 0	–	16	19	pF
		f = 1 MHz; V <sub>R</sub> = 5	–	8	11	pF

1. Non-repetitive current pulse 8/20 μs exponential decay waveform; see Fig.5.
2. Pins 1 and 3 or 2 and 3.
3. Pins 1 and 2.






Fig.2 Non-repetitive peak reverse current as a function of pulse time (square pulse).



$T_j = 25\text{ }^\circ\text{C}$ ;  $f = 1\text{ MHz}$ .

Fig.3 Diode capacitance as a function of reverse voltage; typical values.



$P_{ZSM} = V_{ZSM} \times I_{ZSM}$ .  
 $V_{ZSM}$  is the non-repetitive peak reverse voltage at  $I_{ZSM}$ .

Fig.4 Maximum non-repetitive peak reverse power dissipation as a function of pulse duration (square pulse).







Fig.5 8/20  $\mu\text{s}$  pulse waveform according to IEC 61000-4-5.




unclamped +1 kV ESD voltage waveform  
(IEC 61000-4-2 network)



clamped +1 kV ESD voltage waveform  
(IEC 61000-4-2 network)



unclamped -1 kV ESD voltage waveform  
(IEC 61000-4-2 network)




clamped -1 kV ESD voltage waveform  
(IEC 61000-4-2 network)

MLE219


Fig.6 ESD clamping test set-up and waveforms.

### SOT-883 PACKAGE OUTLINE DIMENSIONS



SYMBOL	DIMENSIONS IN MM		
	MIN	NOM	MAX
A	0.45	0.50	0.55
A1	0.00	—	0.05
D	0.55	0.60	0.65
E	0.95	1.00	1.05
D1	0.45	0.50	0.55
E1	0.20	0.25	0.30
L	0.20	0.25	0.30
b	0.10	0.15	0.20
e	0.35BSC		
e1	0.65BSC		

### Marking



### Ordering information

Order code	Marking code	Package	Baseqty	Deliverymode
PESD3V3L2UM	F2	SOT-883	10000	Tape and reel
PESD5V0L2UM	F1	SOT-883	10000	Tape and reel

## Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.