

EVVOSEMI[®]

THINK CHANGE DO



ESD



TVS



MOS



LDO



Diode



Sensor



DC-DC

Product Specification

▶ Domestic	Part Number	EV1SS184-S1
▶ Overseas	Part Number	1SS184
▶ Equivalent	Part Number	1SS184

"S1" means SOT-23


EV is the abbreviation of name EVVO

Switching Diodes



FEATURES

- Low forward voltage : $V_F(3) = 0.9 \text{ V(Typ.)}$
- Fast reverse recovery time: $t_{rr} = 1.6 \text{ ns(Typ.)}$
- Small Total Capacitance : $C_T = 0.9\text{pF(Typ.)}$

MARKING: B3



SOT-23



Maximum Ratings @ $T_a=25^\circ\text{C}$

Parameter	Symbol	Value	Unit
Peak Reverse voltage	V_{RM}	85	V
DC Blocking Voltage	V_R	80	V
Average Rectified Output Current	I_o	100	mA
Peak forward surge current	I_{FM}	300	mA
Power Dissipation	P_D	150	mW
Junction Temperature	T_J	125	$^\circ\text{C}$
Storage temperature range	T_{STG}	-55 ~ +150	$^\circ\text{C}$

Electrical Characteristics@ $T_a=25^\circ\text{C}$

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse breakdown voltage	V_R	$I_R=100\mu\text{A}$	80			V
Forward voltage	V_{F1}	$I_F=1 \text{ mA}$		0.6		V
	V_{F2}	$I_F=10\text{mA}$		0.72		V
	V_{F3}	$I_F=100\text{mA}$		0.9	1.2	V
Reverse voltage leakage current	I_{R1}	$V_R=30\text{V}$			0.1	μA
	I_{R2}	$V_R=80\text{V}$			0.5	μA
Capacitance between terminals	C_T	$V_R=0\text{V}, f=1\text{MHz}$		0.9	3.0	pF
Reverse recovery time	t_{rr}	$I_F=10\text{mA}$		1.6	4.0	ns

Fig.1 Power Derating Curve




Fig.2 Reverse Characteristics




Fig.3 Forward Characteristics







Fig.4 Capacitance Characteristics



SOT-23 Package Outline Dimensions



The recommended mounting pad size




Marking


Type number	Marking code
1SS184	B3

SOT-23 Packing

1. The method of packaging and dimension are shown as below figure. (Dimension in mm)




SOT-23 Embossed Carrier Tape



Dimensions are in millimeter

Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.