

# EVVOSEMI<sup>®</sup>

THINK CHANGE DO



ESD



TVS



MOS



LDO



Diode



Sensor



DC-DC

## Product Specification


▶ Domestic	Part Number	MCR100-4/-6/-8
▶ Overseas	Part Number	MCR100-4/-6/-8
▶ Equivalent	Part Number	MCR100-4/-6/-8

EV is the abbreviation of name EVVO

## ■ Silicon Controlled Rectifiers

### ■ Features

- Sensitive gate silicon controlled rectifiers
- Reverse blocking thyristors



### ■ Simplified outline(SOT-89)

Pin	Symbol	Description
1	K	Cathode
2	A	Anode
3	G	Gate

### ■ Absolute Maximum Ratings Ta = 25°C

Parameter	Symbols	Value	Units
Peak Repetitive Off-State Voltage <sup>Note4</sup> (T <sub>J</sub> = -40°C to 110°C, Sine Wave, 50 to 60 Hz, Gate Open)	MCR100-4 MCR100-6 MCR100-8 V <sub>DRM</sub> , V <sub>RRM</sub>	200 400 600	V
On-State RMS Current	I <sub>T(RMS)</sub>	0.8	A
Peak Non-Repetitive Surge Current (1/2 Cycle, Sine Wave, 60 Hz, T <sub>J</sub> = 25°C)	I <sub>TSM</sub>	8	A
Circuit Fusing Considerations (t = 8.3ms)	I <sup>2</sup> t	0.415	A <sup>2</sup> s
Forward Peak Gate Power (Pulse Width ≤ 1 μs)	P <sub>GM</sub>	0.1	W
Forward Average Gate Power (t = 8.3ms)	P <sub>G(AV)</sub>	0.1	W
Peak Gate Current – Forward (Pulse Width ≤ 1 μs)	I <sub>GM</sub>	1	A
Peak Gate Voltage – Reverse (Pulse Width ≤ 1 μs)	V <sub>GRM</sub>	5	V
Operating Junction Temperature Range	T <sub>J</sub>	- 40 to + 110	°C
Storage Temperature Range	T <sub>STG</sub>	- 40 to + 150	°C

**■ Electrical Characteristics Ta = 25°C**

Parameter	Symbols	Max.	Units
Peak Forward or Reverse Blocking Current <sup>Note2</sup> at $V_D = \text{Rated } V_{DRM}$ and $V_{RRM}$ , $R_{GK} = 1K\Omega$	$I_{DRM}, I_{RRM}$	10	$\mu A$
Peak Forward On-State Voltage <sup>Note1</sup> at $I_{TM} = 0.8 A$	$V_{TM}$	1.7	V
Gate Trigger Current <sup>Note3</sup> at $V_{AK} = 7 V$ , $R_L = 100 \Omega$	$I_{GT}$	200	$\mu A$
Holding Current <sup>Note2</sup> at $V_{AK} = 7 V$ , Initiating Current = 20 mA	$I_H$	$T_C = 25^\circ C$ 5 $T_C = -40^\circ C$ 10	mA
Latch Current at $V_{AK} = 7 V$ , $I_g = 1 mA$	$I_L$	$T_C = 25^\circ C$ 10 $T_C = -40^\circ C$ 15	mA
Gate Trigger Voltage <sup>Note3</sup> at $V_{AK} = 7 V$ , $R_L = 100 \Omega$	$V_{GT}$	$T_C = 25^\circ C$ 0.8 $T_C = -40^\circ C$ 1.2	V

**Note:**

1)Indicates pulse test width  $\leq 1 ms$ , duty cycle  $\leq 1\%$

2) $R_{GK} = 1 K\Omega$  included in measurement

3)Does not include  $R_{GK}$  in measurement

4) $V_{DRM}$  and  $V_{RRM}$  for all types can be applied on continuous basis. Ratings apply for zero negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.




Figure 1. Typical Gate Trigger Current versus Junction Temperature




Figure 2. Typical Gate Trigger Voltage versus Junction Temperature




Figure 3. Typical Holding Current versus Junction Temperature




Figure 4. Typical Latching Current versus Junction Temperature




Figure 5. Typical RMS Current Derating





Figure 6. Typical On-State Characteristics

■ SOT-89



**DIMENSIONS** (mm are the original dimensions)

UNIT	A	$b_{p1}$	$b_{p2}$	$b_{p3}$	c	D	E	e	$e_1$	$H_E$	$L_p$	w
mm	1.6 1.4	0.48 0.35	0.53 0.40	1.8 1.4	0.44 0.23	4.6 4.4	2.6 2.4	3.0	1.5	4.25 3.75	1.2 0.8	0.13

## Disclaimer

EVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVOSEMI.

The EVVO logo and EVOSEMI are trademarks of EVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.